


Nom. bore	Type	Max. static working pressure [bar/psi]			C _v value		Cross section [mm ²]	Page
		steel	brass	st. st.	both sides self sealing	one side self sealing		
2.5	06-003	–	100	–	–	0.165	5	11
3	LP-003	–	200	–	–	0.21	8	12
3	07-003	–	200	200	0.14	–	7.1	13
4	LP-004	60	20	20	0.3	0.36	13	14
4	LV-004	–	20	20	0.3	–	13	15
6	LP-006	60	40	40	0.73	1.13	30	16 – 17
6	SP-006	100	60	60	0.77	1.1	30	18 – 19
7	LP-007	50	40	40	1.17	1.5	40	20 – 21
9	SP-009	100	40	40	2.1	2.41	64	22 – 23
12	LP-012	50	30	30	3.28	4.34	120	24 – 25
19	LP-019	50	30	30	8.4	11.6	300	26 – 27
32	LP-032	30	30	30	23.8	29.4	800	28 – 29
50	LP-050	30	20	20	59	68	2000	30 – 31
Performance diagrams								32 – 33
Multiway connectors								34


Types LV-004, LP-006, SP-006, LP-007, SP-009 and LP-012 in stainless steel are supplied with gripping grooves instead of knurling as a standard feature



10 Low pressure Series LP

The series LP offers couplings with one side or both sides self sealing and valves in nominal bore 2.5 to 50 mm. This series is supplied in different materials and surface coatings.

With the exception of types LP-032 and LP-050 the LP series is also suitable for vacuum applications (in connected condition).



characteristic features:
 - automatic lock (one hand operation)
 - mini coupling










materials:
standard:
 23 = brass, nickel plated

seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

optional features:
 OV = without valve
 (no one hand operation)

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ◐ Medium ○ Long

	Part No.	Conne- tion A	brass nickel plated	A ₁	SW	SW ₁	l	l ₁	d	d ₁	t	n	weight [g]
				A ₂		SW ₂		l ₂		d ₂			
Self sealing couplings	 male thread	06-003-0-XX001-23-	●		9		26,5		10		6		8
		06-003-0-XX010-23-	●		11		30,5		10		10		12
	 female thread	06-003-0-XX015-23-	●		9		28		10		7		11
	 hose connection	06-003-0-SL004-23-	●		9		39,5		10		19		10
	 re-usable hose connection with swivel nut for plastic pipes	06-003-0-SW003-23-	●	M 7 x 0,5	9	7	32,5	9	10	8	12		11
		06-003-0-SW004-23-	●	M 10 x 1	11	13	36,5	13,5	10	14,3	16		21
 re-usable hose connection with swivel nut for plastic pipes and with counter nut for bulkhead mounting, max. thickness 4 mm	06-003-0-XX017-23-	○	M 7 x 0,5 M 7 x 0,5	9	7 11	45,5	9 3	10	8 12	25		24	
	06-003-0-XX006-23-	●	M 10 x 1 M 10 x 1	11	13 17	45,5	13,5 5	10	14,3 18,9	25		25	
Thru type adaptors	 male thread	06-003-1-XX001-23	●		9		19		9,9		6	9	4
		06-003-1-WR010-23	◐		11		21		12		8	9	6
	 female thread	06-003-1-XX015-23	◐		9		18		9,9		7	9	5
	 hose connection	06-003-1-SL004-23	●				29,5		6		19	9	3
	 re-usable hose connection with swivel nut for plastic pipes	06-003-1-SW003-23	●	M 7 x 0,5	8	7	25	9	8,9	8	12	9	5
06-003-1-SW004-23		◐	M 10 x 1	11	13	29	13,5	12	14,3	16	9	17	

characteristic features:
- automatic lock (one hand operation)










materials:
standard:
23 = brass, nickel plated

seal qualities:
1 = NBR
2 = FKM
4 = EPDM

optional features:
OV = without valve

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ○ Medium ○ Long

	Part No.	Connection A/A ₁	brass nickel-plated	pipe od	n.b.	SF/SF ₁	l	l ₁	d	d ₁	t	n	Weight [g]	
Self sealing couplings	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LP-003-0-WR010-23-.	BSPP 1/8"	●			14 —	32,5	15		8		32	
	 male thread to DIN ISO 228 for bulkhead mounting (max. thickness 2 mm), complete with counternut	LP-003-0-XX016-23-.	BSPP 1/4"	○			17 22	34	6	15	23,9	15		46
	 re-usable hose connection with swivel nut for plastic pipes	LP-003-0-SW004-23-.	OD 6 ID 4 mm M 10 x 1	○			14 13	40,5	13,5	15	14,3	16		50
	 metric male thread with 24° sealing cone to DIN 2353 (light duty series L)	LP-003-0-L0612-23-.	M 12 x 1,5	○	6	4	14 —	34,5		15		10		38
	 hose connection	LP-003-0-SL004-23-.	4 mm	●			14 —	44,5		15		19		36
	 male thread with 4 mm hose connection for bulkhead mounting (max. thickness 2 mm) complete with counternut	LP-003-0-XX004-23-.	4 mm M 14 x 1,5	●			17 19	54,5	6	15	25,4	19		50
Thru type adaptors	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LP-003-1-WR010-23	BSPP 1/8"	●			12 —	25	13,8		8	13	9	
	 re-usable hose connection with swivel nut for plastic pipes	LP-003-1-SW004-23	OD 6 ID 4 mm M 10 x 1	○			12 13	33	13,5	13,2	14,3	16	13	17
	 hose connection	LP-003-1-SL004-23	4 mm	●				35		8		19	13	4

characteristic features:
- automatic lock (one hand operation)









materials:
standard:
23 = brass, nickel plated

seal qualities:
1 = NBR
2 = FKM
4 = EPDM

special materials:
1 = stainless steel 1.4404/1.4571 or similar

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ◐ Medium ○ Long

	Part No.	Connection A/ A ₁	brass nickel plated	AISI 316 ti//1.4571	pipe od	n.b.	d	d ₁	SW SW ₁	l	l ₁	t	n	Weight [g]
Self sealing couplings	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	07-003-0-WR010-...-	BSPP 1/8"	●	○		15		12 —	39,8		8		32
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	07-003-0-WR510-...-	BSPP 1/8"	○	○		15		12 —	37,8		9		30
	 re-usable hose connection with swivel nut for plastic pipes	07-003-0-SW004-...-	OD 6 ID 4 mm M 10 x 1	○	○		15	14,3	12 13	47,8	13,5	16		41
	 hose connection	07-003-0-SL004-...-	4 mm	○	○		15		12 —	51,8		19		32
Self sealing adaptors	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	07-003-2-WR010-...-	BSPP 1/8"	●	○		13,2		12 —	38		8	15	18
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	07-003-2-WR510-...-	BSPP 1/8"	○	○		13,2		12 —	36		9	15	15
	 re-usable hose connection with swivel nut for plastic pipes	07-003-2-SW004-...-	OD 6 ID 4 mm M 10 x 1	○	○		13,2	14,3	12 13	46	13,5	16	15	27
	 hose connection	07-003-2-SL004-...-	4 mm	○	○		13,2		12 —	50		19	15	17

optional features:
OV = without valve

see also type LV-004 in extended version and with non squirt feature (in stainless steel or alternatively brass passivated)













materials:
standard:
11 = steel, zinc plated
21 = brass, passivated
23 = brass, nickel plated

special materials:
31 = aluminium anodized silver
13 = steel, chem. nickel plated
24 = brass, chem. nickel plated

seal qualities:
1 = NBR
2 = FKM
4 = EPDM

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ● Medium ○ Long

	Part No.	Connection A/ A ₁	steel zinc-plated	brass passivated	brass nickel-plated	pipe od	n.b.	d	d ₁	SF/SF ₁	l/l ₁	t	n	Weight [g]
Self sealing couplings	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LP-004-0-WR010-...	BSPP 1/8"	●	●	●		18		14/-	45,5/-	8		50
		LP-004-0-WR013-...	BSPP 1/4"	●	●	○		18		14/-	46,5/-	11		55
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LP-004-0-WR510-...	BSPP 1/8"	●	●	●		18		14/-	45,5/-	9		55
		 re-usable hose connection with swivel nut for plastic pipes	LP-004-0-SW004-...	OD 6 ID 4 mm M 10 x 1		●	○		18	14,3	14/13	51,5/13,5	16	
	 hose connection		LP-004-0-SL004-...	4 mm	●	●	●		18		12/-	50/-	19	15
		LP-004-0-SL006-...	6 mm	●	●	●		18		14/-	60,5/-	25		50
Self sealing adaptors	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LP-004-2-WR010-...	BSPP 1/8"	●	●	●		18		14/-	45/-	8	16	36
		LP-004-2-WR013-...	BSPP 1/4"	●	●	○		18		14/-	46/-	11	16	41
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	P-004-2-WR510-...	BSPP 1/8"	●	●	●		18		14/-	45/-	9	16	41
		 re-usable hose connection with swivel nut for plastic pipes	LP-004-2-SW004-...	OD 6 ID 4 mm		●	○		18	14,3	14/13	51/13,5	16	16
	 hose connection		LP-004-2-SL004-...	4 mm	●	●	●		18		14/-	53/-	18	16
		LP-004-2-SL006-...	6 mm	●	●	●		18		14/-	60/-	25	16	36
Thru type adaptors	 British standard pipe parallel (BSPP) male thread to DIN ISO 228 metric ISO fine-pitch thread, male to DIN 13 with pitch 1,0 mm	LP-004-1-WR010-...	BSPP 1/8"	●	●	●		16,2		14/-	29/-	8	16	15
		LP-004-1-WR013-...	BSPP 1/4"	●	●	○		16,2		14/-	32/-	11	16	20
		LP-004-1-4M010-...	M 10 x 1		●	○		14,8		13/-	28/-	8	16	17
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LP-004-1-WR510-...	BSPP 1/8"	●	●	○		16,2		14/-	29/-	9	16	18
		 re-usable hose connection with swivel nut for plastic pipes	LP-004-1-SW004-...	OD 6 ID 4 mm		○	○		13,2	14,3	12/13	37/13,5	16	16
	 hose connection		LP-004-1-SL004-...	4 mm		○	○		12			37/-	18	16
LP-004-1-SL006-...		6 mm	●	●	○		12			44/-	25	16	11	

characteristic features:

- extended version
- non squirt feature
- stainless steel version 1.4404/1.4571 or similar in smooth variant with gripping grooves instead of knurling

materials:

- standard:**
 21 = brass, passivated
 01 = stainless steel 1.4404/1.4571 or similar

seal qualities:









- 1 = NBR
- 2 = FKM
- 4 = EPDM

optional features:

OV = without valve

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ○ Medium ○ Long

	Part No.	Connection A/A ₁	brass passivated	AISI 316 ti/1.4571	pipe od	n.b.	d	d ₁	AF/AF ₁	l	l ₁	t	n	Weight [g]	
Self sealing couplings	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LV-004-0-WR010-...-	BSPP 1/8"	●	○		18		14/-	50,5		8		55	
		LV-004-0-WR013-...-	BSPP 1/4"	●	○		18		14/-	51,5		11		60	
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LV-004-0-WR510-...-	BSPP 1/8"	●	○		18		14/-	50,5		9		60	
		 re-usable hose connection with swivel nut for plastic pipes	LV-004-0-SW004-...-	OD 6 ID 4 mm	●		6	4	18	14,3	14/13	56,5	13,5	16	
	 hose connection		LV-004-0-SL004-...-	4 mm	●	○			18		14/-	58,5		18	
		LV-004-0-SL006-...-	6 mm	●	○			18		14/-	65,5		25		55
Self sealing adaptors	 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LV-004-2-WR010-...-	BSPP 1/8"	●	○		18		14/-	50		8	21	38	
		LV-004-2-WR013-...-	BSPP 1/4"	●	○		18		14/-	51		11	21	43	
	 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LV-004-2-WR510-...-	BSPP 1/8"	●	○			18		14/-	50		9	21	42
		 re-usable hose connection with swivel nut for plastic pipes	LV-004-2-SW004-...-	OD 6 ID 4 mm M 10 x 1	●				18	14,3	14/13	56	13,5	16	21
	 hose connection		LV-004-2-SL004-...-	4 mm	●	○			18		14/-	58		18	21
		LV-004-2-SL006-...-	6 mm	●	○			18		14/-	65		25	21	38

characteristic features:
 - non squirt feature
 - can be coupled with type KL-006 (plastic version)
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead of knurling

optional features:
 OV = without valve
 SI = with additional axial safety lock
 (outer diameter 29 mm)
 VH = with locking aid













materials:
standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated
 31 = aluminium anodized silver

seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9










Availability: ● Short ○ Medium ○ Long

Self sealing couplings	Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-006-0-WR013-...	BSPP 1/4"	●	●	●	○				25	19	58	11		110
	LP-006-0-WR017-...	BSPP 3/8"	●	●	●	○				25	19	59	12		120
	LP-006-0-WR021-...	BSPP 1/2"	●	●	●	○				25	22	62	15		140
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-006-0-WE017-...	BSPP 3/8"	●							25	27	64	12		160
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	LP-006-0-VR013-...	BSPP 1/4"	○			○			6	25	19	58	11		110
	LP-006-0-VR017-...	BSPP 3/8"	○			○			6	25	19	59	12		120
 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-006-0-D0614-...	M 14 x 1,5	●			○			6	25	19	57	10		110
 <p>metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm</p>	LP-006-0-DV008-...	M 14 x 1,5	○			○			6	25	19	79	32		130
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-006-0-L0612-...	M 12 x 1,5	●			○	L	6	4	25	19	57	10	110
		LP-006-0-L0814-...	M 14 x 1,5	●			○	L	8	6	25	19	57	10	110
		LP-006-0-L1016-...	M 16 x 1,5	●			○	L	10	8	25	19	58	11	110
		LP-006-0-L1218-...	M 18 x 1,5	○			○	L	12	10	25	19	58	11	110
		LP-006-0-S0816-...	M 16 x 1,5	○			○	S	8	4	25	19	59	12	120
		LP-006-0-S1018-...	M 18 x 1,5	●			○	S	10	6	25	19	59	12	120
LP-006-0-S1220-...	M 20 x 1,5	●			○	S	12	8	25	22	59	12	130		
 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S), extended thread, max. bulkhead thickness 10 mm</p>	LP-006-0-LV008-...	M 14 x 1,5	●			○	L	8	6	25	19	79	32	130	
	LP-006-0-XX211-...	M 16 x 1,5	○			○	L	10	8	25	19	79	32	140	
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-006-0-WR513-...	BSPP 1/4"	●	●	●	○				25	19	57	13	120	
	LP-006-0-WR517-...	BSPP 3/8"	●	●	●	○				25	22	58	14	120	
 <p>hose connection</p>	LP-006-0-SL006-...	6 mm	●	●	●	○				25	19	72	25	110	
	LP-006-0-SL009-...	9 mm	●	●	●	○				25	19	77	30	110	
	LP-006-0-SL011-...	11 mm	●	●	●	○				25	19	77	30	120	
	LP-006-0-SL013-...	13 mm	●	●	●	○				25	19	77	30	130	
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-006-2-WR013-...	BSPP 1/4"	●	●	●	○				25	19	56	11	20	85
	LP-006-2-WR017-...	BSPP 3/8"	●	●	●	○				25	19	57	12	20	90
	LP-006-2-WR021-...	BSPP 1/2"	●	●	●	○				25	22	60	15	20	110
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-006-2-WE017-...	BSPP 3/8"	●							25	27	62	12	20	130
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	LP-006-2-VR013-...	BSPP 1/4"	○			○			6	25	19	56	11	20	85
	LP-006-2-VR017-...	BSPP 3/8"	○			○			6	25	19	57	12	20	90

Self sealing couplings

Self sealing adaptors

Availability: ● Short ● Medium ○ Long

	Part No.	Conne- tion A	steel zinc	brass	passivated	brass chrome	AISI 316 ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]	
			plated			plated											
Self sealing adaptors	 metric male thread with 60° sealing cone to DIN 7631	LP-006-2-D0614-...-	M 14 x 1,5	●						6	25	19	55	10	20	85	
	 metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm	LP-006-2-DV008-...-	M 14 x 1,5	○						6	25	19	77	32	20	100	
	 metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)	LP-006-2-L0612-...-	M 12 x 1,5	●					L	6	4	25	19	55	10	20	80
		LP-006-2-L0814-...-	M 14 x 1,5	●					L	8	6	25	19	55	10	20	85
		LP-006-2-L1016-...-	M 16 x 1,5	●					L	10	8	25	19	56	11	20	85
		LP-006-2-L1218-...-	M 18 x 1,5	○					L	12	10	25	19	56	11	20	85
		LP-006-2-S0816-...-	M 16 x 1,5	○					S	8	4	25	19	57	12	20	90
		LP-006-2-S1018-...-	M 18 x 1,5	●					S	10	6	25	19	57	12	20	90
	LP-006-2-S1220-...-	M 20 x 1,5	●					S	12	8	25	22	57	12	20	100	
	 metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S), extended thread, max. bulkhead thickness 10 mm	LP-006-2-LV008-...-	M 14 x 1,5	●					L	8	6	25	19	77	32	20	100
LP-006-2-XX211-...-		M 16 x 1,5	○					L	10	8	25	19	77	32	20	110	
 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LP-006-2-WR513-...-	BSPP 1/4"	●	●	●	○					25	19	55	13	20	90	
	LP-006-2-WR517-...-	BSPP 3/8"	●	●	●	○					25	22	56	14	20	95	
 hose connection	LP-006-2-SL006-...-	6 mm	●	●	●	○					25	19	70	25	20	80	
	LP-006-2-SL009-...-	9 mm	●	●	●	○					25	19	75	30	20	85	
	LP-006-2-SL011-...-	11 mm	●	●	●	○					25	19	75	30	20	90	
	LP-006-2-SL013-...-	13 mm	●	●	●	○					25	19	75	30	20	100	
 British standard pipe parallel (BSPP) male thread to DIN ISO 228	LP-006-1-WR010-..	BSPP 1/8"	●	○	○	○					15,5	14	34	8	20	22	
	LP-006-1-WR013-..	BSPP 1/4"	●	●	●	○					15,5	14	38	11	20	25	
	LP-006-1-WR017-..	BSPP 3/8"	●	●	○	○					21	19	40,5	12	20	39	
 British standard pipe parallel (BSPP) female thread to DIN ISO 228	LP-006-1-WR510-..	BSPP 1/8"	○	○	○	○					16,5	15	31	9	20	20	
	LP-006-1-WR513-..	BSPP 1/4"	●	●	●	○					18,9	17	36	13	20	28	
	LP-006-1-WR517-..	BSPP 3/8"	●	●	●	○					24	22	38	14	20	44	
 hose connection	LP-006-1-SL006-...	6 mm	●	●	●	○					12		46		20	16	
	LP-006-1-SL009-...	9 mm	●	●	●	○					12		51		20	20	
	LP-006-1-SL011-...	11 mm	●	●	●	○					16		53		20	31	
	LP-006-1-SL013-...	13 mm	●	●	●	○					16		53		20	41	

characteristic features:
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead
 knurling

optional features:
 OV = without valve

materials:
 standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:
 31 = aluminium anodized silver
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated













seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

Please note the
 technical data on
 pages 2 - 7, 32 - 33 and the
 max. working pressures
 on page 9










Availability: ● Short ○ Medium ○ Long

Self sealing couplings

Self sealing adaptors

	Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	SP-006-0-WR013-...	BSPP 1/4"	●	●	●	○				22	19	58	11		90
	SP-006-0-WR017-...	BSPP 3/8"	●	●	●	○				22	19	59	12		95
	SP-006-0-WR021-...	BSPP 1/2"	●	●	●	○				22	22	62	15		120
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	SP-006-0-WE017-...	BSPP 3/8"	●							22	27	64	12		130
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	SP-006-0-VR013-...	BSPP 1/4"	○			○		6	22	19	58	11		90	
	SP-006-0-VR017-...	BSPP 3/8"	○			○		6	22	19	59	12		95	
 <p>metric male thread with 60° sealing cone to DIN 7631</p>	SP-006-0-D0614-...	M 14 x 1,5	○			○		6	22	19	57	10		85	
 <p>metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm</p>	SP-006-0-DV008-...	M 14 x 1,5	○			○		6	22	19	79	32		105	
 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	SP-006-0-L0612-...	M 12 x 1,5	●			○	L	6	4	22	19	57	10		85
	SP-006-0-L0814-...	M 14 x 1,5	●			○	L	8	6	22	19	57	10		85
	SP-006-0-L1016-...	M 16 x 1,5	●			○	L	10	8	22	19	58	11		90
	SP-006-0-L1218-...	M 18 x 1,5	○			○	L	12	10	22	19	58	11		90
	SP-006-0-S0816-...	M 16 x 1,5	○			○	S	8	4	22	19	59	12		90
	SP-006-0-S1018-...	M 18 x 1,5	○			○	S	10	6	22	19	59	12		95
	SP-006-0-S1220-...	M 20 x 1,5	●			○	S	12	8	22	22	59	12		100
 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S), extended thread, max. bulkhead thickness 10 mm</p>	SP-006-0-LV008-...	M 14 x 1,5	●			○	L	8	6	22	19	79	32		100
	SP-006-0-XX211-...	M 16 x 1,5	○			○	L	10	8	22	19	79	32		110
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	SP-006-0-WR513-...	BSPP 1/4"	●	●	●	○				22	19	57	13		95
	SP-006-0-WR517-...	BSPP 3/8"	●	●	●	○				22	22	58	14		100
 <p>hose connection</p>	SP-006-0-SL006-...	6 mm	●	●	●	○				22	19	72	25		85
	SP-006-0-SL009-...	9 mm	●	●	●	○				22	19	77	30		90
	SP-006-0-SL011-...	11 mm	●	●	●	○				22	19	77	30		95
	SP-006-0-SL013-...	13 mm	●	●	●	○				22	19	77	30		110
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	SP-006-2-WR013-...	BSPP 1/4"	●	●	●	○				22	19	56	11	20	70
	SP-006-2-WR017-...	BSPP 3/8"	●	●	●	○				22	19	57	12	20	75
	SP-006-2-WR021-...	BSPP 1/2"	●	●	●	○				22	22	60	15	20	100
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	SP-006-2-WE017-...	BSPP 3/8"	●							22	27	62	12	20	110
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	SP-006-2-VR013-...	BSPP 1/4"	○			○		6	22	19	56	11	20	70	
	SP-006-2-VR017-...	BSPP 3/8"	○			○		6	22	19	57	12	20	75	

Availability: ● Short ○ Medium ○ Long

	Part No.	Conne- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
Self sealing adaptors	 metric male thread with 60° sealing cone to DIN 7631	SP-006-2-D0614-... M 14 x 1,5	○			○			6	22	19	55	10	20	70
	 metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm	SP-006-2-DV008-... M 14 x 1,5	○			○			6	22	19	77	32	20	90
	 metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)	SP-006-2-L0612-... M 12 x 1,5	●			○	L	6	4	22	19	55	10	20	70
		SP-006-2-L0814-... M 14 x 1,5	●			○	L	8	6	22	19	55	10	20	70
		SP-006-2-L1016-... M 16 x 1,5	●			○	L	10	8	22	19	56	11	20	70
		SP-006-2-L1218-... M 18 x 1,5	○			○	L	12	10	22	19	56	11	20	70
		SP-006-2-S0816-... M 16 x 1,5	○			○	S	8	4	22	19	57	12	20	75
		SP-006-2-S1018-... M 18 x 1,5	○			○	S	10	6	22	19	57	12	20	75
		SP-006-2-S1220-... M 20 x 1,5	○			○	S	12	8	22	22	57	12	20	85
	 metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S), extended thread, max. bulkhead thickness 10 mm	SP-006-2-LV008-... M 14 x 1,5	○			○	L	8	6	22	19	77	32	20	85
SP-006-2-XX211-... M 16 x 1,5		○			○	L	10	8	22	19	77	32	20	95	
 British standard pipe parallel (BSPP) female thread to DIN ISO 228	SP-006-2-WR513-... BSPP 1/4"	●	●	●	○				22	19	55	13	20	75	
	SP-006-2-WR517-... BSPP 3/8"	●	●	●	○				22	22	56	14	20	80	
 hose connection	SP-006-2-SL006-... 6 mm	○	○	○	○				22	19	70	25	20	70	
	SP-006-2-SL009-... 9 mm	●	●	●	○				22	19	75	30	20	70	
	SP-006-2-SL011-... 11 mm	○	○	○	○				22	19	75	30	20	80	
	SP-006-2-SL013-... 13 mm	○	○	○	○				22	19	75	30	20	90	
 British standard pipe parallel (BSPP) male thread to DIN ISO 228	SP-006-1-WR010-... BSPP 1/8"	●	●	●	○				15,5	14	34	8	20	20	
	SP-006-1-WR013-... BSPP 1/4"	●	●	●	○				15,5	14	37	11	20	23	
	SP-006-1-WR017-... BSPP 3/8"	●	●	●	○				21,9	19	38	12	20	37	
 British standard pipe parallel (BSPP) female thread to DIN ISO 228	SP-006-1-WR513-... BSPP 1/4"	●	○	○	○				19,6	17	36	13	20	26	
	SP-006-1-WR517-... BSPP 3/8"	○	○	○	○				24	22	37	14	20	40	
 hose connection	SP-006-1-SL006-... 6 mm	●	○	○	○				11		46		20	13	
	SP-006-1-SL009-... 9 mm	●	○	○	○				11		51		20	18	

Self sealing adaptors

Thru type adaptors

characteristic features:
 - non squirt feature
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead knurling

optional features:
 OV = without valve
 S = with additional axial safety lock
 (outer diameter 34 mm)
 VH = with locking aid

materials:
standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar









special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated

seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM




Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ○ Medium ○ Long

Self sealing couplings

	Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-007-0-WR017-... LP-007-0-WR021-...	BSPP 3/8" BSPP 1/2"	● ●	● ●	● ●	○ ○				30 30	24 24	68 71	12 15		200 210
	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-007-0-WE017-...	BSPP 3/8"	●						30	27	71	12		220
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>		LP-007-0-VR017-...	BSPP 3/8"	○					7	30	24	68	12		190
	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-007-0-D0816-...	M 16 x 1,5	○					8	30	24	67	11		200
 <p>metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm</p>		LP-007-0-DV010-...	M 16 x 1,5	○					8	30	24	89,5	33,5		210
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-007-0-L1016-... LP-007-0-L1218-... LP-007-0-S1018-... LP-007-0-S1220-...	M 16 x 1,5 M 18 x 1,5 M 18 x 1,5 M 20 x 1,5	● ● ● ●			○ ○ ○ ○	L L S S	10 12 10 12	8 10 6 8	30 30 30 30	24 24 24 24	67 67 68 68	11 11 12 12	
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>		LP-007-0-WR517-... LP-007-0-WR521-...	BSPP 3/8" BSPP 1/2"	● ●	● ●	● ○				30 30	24 27	68 71	14 17		210 230
		 <p>hose connection</p>	LP-007-0-SL009-... LP-007-0-SL011-... LP-007-0-SL013-...	9 mm 11 mm 13 mm	● ● ●	● ● ●	● ● ●	○ ○ ○			30 30 30	24 24 24	86 86 86	30 30 30	

Self sealing adaptors

 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-007-2-WR017-... LP-007-2-WR021-...	BSPP 3/8" BSPP 1/2"	● ●	● ●	● ○				30 30	24 24	66 69	12 15	23,3 23,3	150 170
	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-007-2-WE017-...	BSPP 3/8"	●					30	27	69	12	23,3	170
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>		LP-007-2-VR017-...	BSPP 3/8"	○					7	30	24	66	12	23,3

Availability: ● Short ● Medium ○ Long

	Part No.	Conne- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
Self sealing adaptors	LP-007-2-D0816-...-	M 16 x 1,5	○			○			8	30	24	65	11	23,3	150
	LP-007-2-DV010-...-	M 16 x 1,5	○			○			8	30	24	87,5	33,5	23,3	160
	LP-007-2-L1016-...-	M 16 x 1,5	●			○	L	10	8	30	24	65	11	23,3	140
	LP-007-2-L1218-...-	M 18 x 1,5	●			○	L	12	10	30	24	65	11	23,3	140
	LP-007-2-S1018-...-	M 18 x 1,5	●			○	S	10	6	30	24	66	12	23,3	150
	LP-007-2-S1220-...-	M 20 x 1,5	●			○	S	12	8	30	24	66	12	23,3	150
	LP-007-2-WR517-...-	BSPP 3/8"	●	●	●	●				30	24	66	14	23,3	160
	LP-007-2-WR521-...-	BSPP 1/2"	●	●	●	○				30	27	69	17	23,3	180
	LP-007-2-SL009-...-	9 mm	●	●	●	○				30	24	84	30	23,3	150
	LP-007-2-SL011-...-	11 mm	●	●	●	○				30	24	84	30	23,3	150
LP-007-2-SL013-...-	13 mm	●	●	●	●				30	24	84	30	23,3	160	
Thru type adaptors	LP-007-1-WR013-...-	BSPP 1/4"	●	○	○	○				18,9	17	40,5	11	23,3	35
	LP-007-1-WR017-...-	BSPP 3/8"	●	○	○	○				21	19	41,5	12	23,3	45
	LP-007-1-WR021-...-	BSPP 1/2"	●	●	●	○				26,7	24	44,5	15	23,3	70
	LP-007-1-WR513-...-	BSPP 1/4"	●	○	○	○				18,9	17	40,5	13	23,3	37
	LP-007-1-WR517-...-	BSPP 3/8"	●	●	●	○				24	22	41,5	14	23,3	55
	LP-007-1-WR521-...-	BSPP 1/2"	●	●	●	○				30	27	44,5	17	23,3	75
	LP-007-1-SL009-...-	9 mm	●	●	○	○						54,5	30	23,3	29
	LP-007-1-SL011-...-	11 mm	●	●	●	○				14		56,5	30	23,3	37
	LP-007-1-SL013-...-	13 mm	●	●	●	○				18		56,5	30	23,3	46

Series LP

characteristic features:
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead
 knurling

optional features:
 OV = without valve







materials:
 standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated




seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

Please note the
 technical data on
 pages 2 - 7, 32 - 33 and the
 max. working pressures
 on page 9

Availability: ● Short ○ Medium ○ Long

	Part No.	Connec- tion A	steel zinc	brass	brass chrome	AISI 316 Ti/	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]	
			plated	passivated	plated	1.4571										
Self sealing couplings	 <p>British stan- dard pipe parallel (BSPP) male thread to DIN ISO 228</p>	SP-009-0-WR017-...- SP-009-0-WR021-...-	●	●	○	○				28	25	71	12		180	
		BSPP 3/8" BSPP 1/2"	●	●	○	○				28	25	71	15		190	
	 <p>British stan- dard pipe parallel (BSPP) fe- male thread to DIN ISO 228</p>	SP-009-0-WR521-...-	BSPP 1/2"	●	●	○	○				28	27	71	17		200
 <p>hose connection</p>	SP-009-0-SL013-...-	13 mm	●	●	○	○				28	25	86	30		180	
Self sealing adaptors	 <p>British stan- dard pipe parallel (BSPP) male thread to DIN ISO 228</p>	SP-009-2-WR017-...-Z02 SP-009-2-WR021-...-Z02	●	●	○	○				28	25	69,5	12	23,5	120	
		BSPP 3/8" BSPP 1/2"	●	●	○	○				28	25	69,5	15	23,5	130	
	 <p>British stan- dard pipe parallel (BSPP) fe- male thread to DIN ISO 228</p>	SP-009-2-WR521-...-Z02	BSPP 1/2"	●	●	○	○				28	27	69,5	17	23,5	140
	 <p>hose connection</p>	SP-009-2-SL013-...-Z02	13 mm	●	●	○	○				28	25	84,5	30	23,5	130

Availability: ● Short ● Medium ○ Long

	Part No.	Conne- tion A	steel zinc	brass	passivated	brass chrome	AISI 316 ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
			plated			plated										
Thru type adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p> <p>SP-009-1-WR017-... SP-009-1-WR021-...</p>	BSPP 3/8" BSPP 1/2"	●	●	○	○					21,9 24	19 22	41,5 46,5	12 15	23,5 23,5	40 60
			 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p> <p>SP-009-1-WR521-...</p>	BSPP 1/2"	●	○	○	○					30	27	45	17
	 <p>hose connection</p> <p>SP-009-1-SL013-..</p>	13 mm	○	●	○	○						15		55	30	23,5

characteristic features:
 - non squirt feature
 - can be coupled with type KL-012 (plastic version)
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead of knurling

optional features:
 OV = without valve
 SI = with additional axial safety lock
 (outer diameter 44 mm)
 VH = with locking aid

materials:
standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated







seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9








Availability: ● Short ○ Medium ○ Long

Self sealing couplings

Self sealing adaptors

	Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-012-0-WR021-... LP-012-0-WR026-... LP-012-0-WR033-...	BSPP 1/2" BSPP 3/4" BSPP 1"	● ● ●	● ○ ○	● ○ ○	○ ○ ○				40 40 40	32 32 36	82 84 88	15 17 20		380 410 470
	LP-012-0-WE021-...	BSPP 1/2"	●							40	32	84	14		390
	LP-012-0-VR021-... LP-012-0-VR026-...	BSPP 1/2" BSPP 3/4"	● ●				○ ○		12 12	40 40	32 32	82 84	15 17		380 400
 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-012-0-D1018-... LP-012-0-D1222-...	M 18 x 1,5 M 22 x 1,5	● ●					10 12	40 40	32 32	78 79	11 12		370 380	
	LP-012-0-DV015-...	M 22 x 1,5	○			○			12	40	32	106	39		430
 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-012-0-L1218-... LP-012-0-L1522-... LP-012-0-S1624-...	M 18 x 1,5 M 22 x 1,5 M 24 x 1,5	● ● ●				L L S	12 15 16	10 12 12	40 40 40	32 32 32	78 79 81	11 12 14		370 380 390
	 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-012-0-WR521-... LP-012-0-WR526-...	BSPP 1/2" BSPP 3/4"	● ●	● ●	○ ○				40 40	32 32	81 83	17 19		420 400
		 <p>hose connection</p>	LP-012-0-SL016-... LP-012-0-SL019-...	16 mm 19 mm	● ●	● ●	○ ○				40 40	32 32	102 102	35 35	
 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-012-2-WR021-... LP-012-2-WR026-... LP-012-2-WR033-...	BSPP 1/2" BSPP 3/4" BSPP 1"	● ● ●	● ○ ○	○ ○ ○	○ ○ ○				40 40 40	32 32 36	80 82 86	15 17 20	29,5 29,5 29,5	290 320 380
	LP-012-2-WE021-...	BSPP 1/2"	●							40	32	82	14	29,5	300
	LP-012-2-VR021-... LP-012-2-VR026-...	BSPP 1/2" BSPP 3/4"	● ●				○ ○		12 12	40 40	32 32	80 82	15 17	29,5 29,5	290 310

Availability: ● Short ● Medium ○ Long

	Part No.	Conne- tion A	steel zinc	brass	passivated	brass chrome	AlSi 316 ti/ 1,4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]	
			plated			plated											
Self sealing adaptors	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-012-2-D1018-... LP-012-2-D1222-...	M 18 x 1,5 M 22 x 1,5	● ●						10 12	40 40	32 32	76 77	11 12	29,5 29,5	280 290	
		LP-012-2-DV015-...	M 22 x 1,5	○				○			12	40	32	104	39	29,5	340
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-012-2-L1218-... LP-012-2-L1522-... LP-012-2-S1624-...	M 18 x 1,5 M 22 x 1,5 M 24 x 1,5	● ● ●					L L S	12 15 16	10 12 12	40 40 40	32 32 32	76 77 79	11 12 14	29,5 29,5 29,5	280 290 290
		 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-012-2-WR521-... LP-012-2-WR526-...	BSPF 1/2" BSPF 3/4"	● ●	● ●	● ●	○ ●				40 40	32 32	79 81	17 19	29,5 29,5	330 310
			 <p>hose connection</p>	LP-012-2-SL016-... LP-012-2-SL019-...	16 mm 19 mm	● ●	● ●	● ●	○ ○				40 40	32 32	100 100	35 35	29,5 29,5
Thru type adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-012-1-WR017-... LP-012-1-WR021-... LP-012-1-WR026-...	BSPF 3/8" BSPF 1/2" BSPF 3/4"	● ● ●	○ ● ●	○ ● ●	○ ○ ○				30 30 33	27 27 30	49,5 54,5 54,5	12 15 17	29,5 29,5 29,5	90 100 140	
		 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-012-1-WR521-... LP-012-1-WR526-...	BSPF 1/2" BSPF 3/4"	● ●	○ ○	○ ○	○ ○				30 35,5	27 32	50,5 52,5	17 19	29,5 29,5	100 120
			 <p>hose connection</p>	LP-012-1-SL013-... LP-012-1-SL016-... LP-012-1-SL019-...	13 mm 16 mm 19 mm	● ● ●	● ○ ●	● ○ ●	○ ○ ○				21 21 25		61 66 68,5	30 35 35	29,5 29,5 29,5

Series LP

characteristic features:
 - non squirt feature
 - stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead of knurling

optional features:
 GG= with ring grips (cast aluminium)
 OV= without valve
 SI = with additional axial safety lock
 (outer diameter 58 mm)
 VH= with locking aid

materials:
standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated












seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9








Availability: ● Short ○ Medium ○ Long

Self sealing couplings

Self sealing adaptors









Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
 British standard pipe parallel (BSPP) male thread to DIN ISO 228 LP-019-0-WR026-... LP-019-0-WR033-...	BSPP 3/4" BSPP 1"	●	○	○	○				54	46	100	17		840
		●	●	●	○				54	46	103	20		870
 British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring. LP-019-0-WE026-...	BSPP 3/4"	○							54	46	102	16		850
 BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone LP-019-0-VR026-... LP-019-0-VR033-...	BSPP 3/4" BSPP 1"	○			○			19	54	46	100	17		830
		○			○			19	54	46	103	20		870
 metric male thread with 60° sealing cone to DIN 7631 LP-019-0-D1526-... LP-019-0-D1930-...	M 26 x 1,5 M 30 x 1,5	○			○			15	54	46	95	12		830
		○			○			19	54	46	97	14		830
 metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10 mm LP-019-0-DV022-...	M 30 x 1,5	○			○			19	54	46	128	45		920
 metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S) LP-019-0-L1826-... LP-019-0-L2230-... LP-019-0-S2030-... LP-019-0-S2536-...	M 26 x 1,5 M 30 x 2 M 30 x 2 M 36 x 2	○			○	L	18	16	54	46	95	12		830
		○			○	L	22	20	54	46	97	14		830
		○			○	S	20	16	54	46	99	16		850
		○			○	S	25	20	54	46	101	18		860
 British standard pipe parallel (BSPP) female thread to DIN ISO 228 LP-019-0-WR526-... LP-019-0-WR533-...	BSPP 3/4" BSPP 1"	●	●	○	○				54	46	94	19		890
		●	●	○	○				54	46	98	23		880
 hose connection LP-019-0-SL019-... LP-019-0-SL025-... LP-019-0-SL028-...	19 mm 25 mm 28 mm	○	○	○	○				54	46	118	35		850
		○	○	○	○				54	46	123	40		870
		○	○	○	○				54	46	128	45		930
 British standard pipe parallel (BSPP) male thread to DIN ISO 228 LP-019-2-WR026-... LP-019-2-WR033-...	BSPP 3/4" BSPP 1"	●	○	○	○				54	46	96	17	32,5	690
		●	●	○	○				54	46	99	20	32,5	720
 British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring. LP-019-2-WE026-...	BSPP 3/4"	○							54	46	98	16	32,5	700
 BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone LP-019-2-VR026-... LP-019-2-VR033-...	BSPP 3/4" BSPP 1"	○			○			19	54	46	96	17	32,5	690
		○			○			19	54	46	99	20	32,5	720

Availability: ● Short ○ Medium ○ Long

	Part No.	Conne- tion A	steel zinc	brass	passivated	brass chrome	AISI 316 ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]	
			plated			plated											
Self sealing adaptors	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-019-2-D1526-... LP-019-2-D1930-...	M 26 x 1,5 M 30 x 1,5	● ●						15 19	54 54	46 46	91 93	12 14	32,5 32,5	680 680	
		LP-019-2-DV022-...	M 30 x 1,5	○							19	54	46	124	45	32,5	770
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-019-2-L1826-... LP-019-2-L2230-... LP-019-2-S2030-... LP-019-2-S2536-...	M 26 x 1,5 M 30 x 2 M 30 x 2 M 36 x 2	● ● ● ●				L L S S	18 22 20 25	16 20 16 20	54 54 54 54	46 46 46 46	91 93 95 97	12 14 16 18	32,5 32,5 32,5 32,5	680 670 690 710	
		 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-019-2-WR526-... LP-019-2-WR533-...	BSPP 3/4" BSPP 1"	● ●	● ●	● ●	○ ○				54 54	46 46	90 94	19 23	32,5 32,5	740 730
			 <p>hose connection</p>	LP-019-2-SL019-... LP-019-2-SL025-... LP-019-2-SL028-...	19 mm 25 mm 28 mm	● ● ●	● ● ●	● ● ●	○ ○ ○				54 54 54	46 46 46	114 119 124	35 40 45	32,5 32,5 32,5
		 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>		LP-019-1-WR021-... LP-019-1-WR026-... LP-019-1-WR033-...	BSPP 1/2" BSPP 3/4" BSPP 1"	● ● ●	● ● ●	● ● ●	○ ○ ○				40 40 40	36 36 36	57,5 59,5 62,5	15 17 20	32,5 32,5 32,5
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-019-1-WR526-... LP-019-1-WR533-...			BSPP 3/4" BSPP 1"	● ●	● ●	● ●	○ ○				40 45	36 41	57,5 61,5	19 23	32,5 32,5	240 250
	 <p>hose connection</p>		LP-019-1-SL019-... LP-019-1-SL025-...	19 mm 25 mm	● ●	○ ●	○ ●	○ ○				32 32		68,5 73,5	35 40	32,5 32,5	180 190

Series LP

Availability: ● Short ● Medium ○ Long

	Part No.	Conne- ction A	steel zinc	brass	passivated	brass chrome	AlSi 316 ti/ 1,4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
			plated		brass	plated										
Self sealing adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-032-2-WR048-... LP-032-2-WR060-...	BSPP 1 1/2" BSPP 2"	● ○	● ○	● ○	○ ○				82 82	75 75	135,5 139,5	22 26	39 39	2460 2500
		 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-032-2-D3245-...	M 45 x 1,5	●						32	82	75	124,5	16	39
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-032-2-S3852-...	M 52 x 2	●				S	38	32	82	75	130,5	22	39	2280
	 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-032-2-WR548-... LP-032-2-WR560-...	BSPP 1 1/2" BSPP 2"	● ●	● ●	● ●	○ ○				82 82	75 75	122,5 126,5	25 29	39 39	2390 2260
		 <p>hose connection</p>	LP-032-2-SL042-...	42 mm	○	○	○	○				82	75	174,5	61	39
Thru type adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-032-1-WR048-... LP-032-1-WR060-...	BSPP 1 1/2" BSPP 2"	● ○	○ ○	○ ○	○ ○				60 72,5	55 65	74,5 78,5	22 26	39 39	600 650
		 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-032-1-WR542-... LP-032-1-WR548-... LP-032-1-WR560-...	BSPP 1 1/4" BSPP 1 1/2" BSPP 2"	● ● ○	○ ○ ●	○ ○ ●	○ ○ ○			60 65 78	55 60 70	71 71 75	25 25 29	39 39 39	610 640 790
	 <p>hose connection</p>	LP-032-1-SL042-..	42 mm	○	○	○	○				54		105	61	39	620

Series LP

optional features:
 SI = with additional axial safety lock
 (outer diameter 116 mm)
 GG = with ring grips (cast aluminium)









materials:
 standard:
 11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM









special materials:
 13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated
 31 = aluminium anodized silver

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ○ Medium ○ Long

	Part No.	Connec- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 Ti/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
Self sealing couplings	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-050-0-WR060-...-.	●	○	○	○				112	100	162	26		5550
		LP-050-0-WR075-...-.	●	○	○	○				112	100	164	30		5560
	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-050-0-D4965-...-.	M 65 x 2						49	112	100	159	18		5440
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-050-0-L4252-...-.	M 52 x 2	●				L	42	36	112	100	158	16	5380
	 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-050-0-WR560-...-.	BSPP 2"	●	○	○	○				112	100	158	29	6150
LP-050-0-WR575-...-.	BSPP 2 1/2"	●	○	○	○					112	100	167	33	5940	
 <p>hose connection</p>	LP-050-0-SL065-...-.	65 mm								112	100	209	75	5970	
Thru type couplings	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-050-4-WR060-...-.	○	○	○	○				112	100	132,5	26	3950	
		LP-050-4-WR075-...-.	○	○	○	○				112	100	136,5	30	4210	
	 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-050-4-WR560-...-.	BSPP 2"	●	○	○	○			112	100	106,5	27	3800	
LP-050-4-WR575-...-.	BSPP 2 1/2"	●	○	○	○				112	100	106,5	31	3640		
 <p>hose connection</p>	LP-050-4-SL065-...-.	65 mm								112	100	181,5	75	4050	

Availability: ● Short ● Medium ○ Long


		Part No.	Connection A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 ti/1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
Self sealing adaptors		British standard pipe parallel (BSPP) male thread to DIN ISO 228 LP-050-2-WR060-...-. LP-050-2-WR075-...-.	BSPP 2" BSPP 2 1/2"	●	○	○	○				112 112	100 100	158 160	26 30	46 46	5010 5020
		metric male thread with 60° sealing cone to DIN 7631 LP-050-2-D4965-...-.	M 65 x 2							49	112	100	155	18	46	4900
		metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S) LP-050-2-L4252-...-.	M 52 x 2	●				L	42	36	112	100	154	16	46	4840
		British standard pipe parallel (BSPP) female thread to DIN ISO 228 LP-050-2-WR560-...-. LP-050-2-WR575-...-.	BSPP 2" BSPP 2 1/2"	●	○	○	○				112 112	100 100	154 163	29 33	46 46	5610 5400
		hose connection LP-050-2-SL065-...-.	65 mm								112	100	205	75	46	5430
Thru type adaptors		British standard pipe parallel (BSPP) male thread to DIN ISO 228 LP-050-1-WR060-...-.	BSPP 2"	●	○	○	○				92	85	88	26	46	1590
		British standard pipe parallel (BSPP) female thread to DIN ISO 228 LP-050-1-WR560-...-.	BSPP 2"	●	○	○	○				92	85	82	29	46	1850
		hose connection LP-050-1-SL065-...-.	65 mm		○	○	○	○			90		131	75	46	2050

Measurement of flow coefficients Cv according to DIN EN 60534


Flow speeds of 8 m/sec should not be exceeded

1 bar = 14,5 PSI

Both sides self sealing



One side self sealing




Measurement of flow coefficients C_v according to DIN EN 60534


Working pressure 6 bar gauge pressure

1 bar = 14,5 PSI

Both sides self sealing



One side self sealing





materials:
 standard:
 11 = steel, zinc plated

seal qualities:
 1 = NBR
 2 = FKM
 4 = EPDM

special materials:
 21 = brass, passivated
 01 = stainless steel 1.4404/1.4571 or similar
 50 = polyamide 11/12, grey (PA)

Availability: ● Short ○ Medium ○ Long

	Part No.	equipped with	steel zinc-plated	D	n.b.	d	d1	l	l1	l2	l3	l4	Weight [g]
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228 and 2 self sealing couplings</p>	2R-006-0-WR517-...-	3/8" BSPP, 2 ssc LP-006	○	25	6				116	81	47,5		430
	2R-007-0-WR521-...-	1/2" BSPP, 2 ssc LP-007	○	30	7				140	96	57		710
	2R-012-0-WR533-...-	1" BSPP, 2 ssc LP-012	○	40	12				178	128	65		1440
 <p>1 thru type adaptors and 2 self sealing couplings, type LP-006</p>	2S-006-0-WR517-...-	1 tta, 2ssc, LP-006	○	25	6	12			116	110	47,5	26	430

